

### **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### Listing of Claims:

1. **(currently amended)** A method ~~[[for]]~~ of embedding a digital watermark on a wavelet lowest subband of an original image, the method comprising the steps of:

wavelet transforming the original image into n levels;

setting a ~~DC component region~~ the wavelet lowest subband of the a multi-stage wavelet-transformed original [[copy]] image as [[to]] a watermark embedment region; [[, and]]

high-frequency filtering an original picture  $LL_n$  of the watermark embedment region to generate a mirror picture  $LL_n'$  from which a high frequency component [[is]] of the original picture  $LL_n$  has been eliminated;

generating (i) index information [[for]] designating a plurality of pixel positions within the watermark embedment region where ~~on which~~ the watermark is to be embedded within the watermark embedment region, and (ii) a watermark sequence of watermark values to be embedded in said pixel positions, respectively;

calculating an embedment strength  $\lambda$  for each said pixel position of the watermark embedment region, considering a variance degree of an original picture  $LL_n$  coefficient value;

~~in case the watermark sequence is sequentially embedded on an embedded position designated by the index information, mutually comparing the original picture  $LL_n$  coefficient value for each said pixel embedded position, selectively altering the original picture  $LL_n$  coefficient value based on (a) [[with]] a corresponding mirror picture  $LL_n'$  coefficient value, and then altering the original picture  $LL_n$  coefficient value depending on (b) the watermark value to be embedded in said~~

pixel position, and (c) with reference to the embedment strength  $\lambda$  of a corresponding said pixel position to embed the watermark; and

selectively embedding the watermark at each said pixel position with the selectively altered original picture  $LL_n$  coefficient value while skipping watermark embedment where the in case the original picture  $LL_n$  coefficient value before and after said altering differs by more than altered by watermark embedment is differentiated above a predetermined value associated with reference to the corresponding embedment strength  $\lambda$  in comparison with the coefficient value before altered, skipping the watermark embedment for the position.

2. **(currently amended)** The method of claim 1, wherein in the step of high frequency filtering component eliminating step, the high-frequency component is eliminated ~~from a picture of the watermark embedment region~~ through Wiener filtering.

3. **(currently amended)** The method of claim 1, wherein in the embedment strength calculating step, the embedment strength  $\lambda$  in every said pixel position in ~~is calculated for the watermark embedment region is calculated~~ according to the following Equations (1) and (2):

$$NVF(i, j) = \frac{\sigma_{\max}^2}{\sigma_{\max}^2 + \theta \sigma^2(i, j)} \dots\dots\dots (1)$$

$$\lambda(i, j) = S_e \bullet (1 - NVF(i, j)) + S_f \bullet NVF(i, j) \dots\dots\dots (2)$$

$\sigma^2(i, j)$  : a local variance value for a peripheral region centering on the position (i,j);

$\sigma_{\max}^2$  : a maximum local variance value in the watermark embedment region;

$S_e, S_f$  and  $\theta$  : embedment strength controlling values.

4. **(currently amended)** The method of claim 1, wherein, in the ~~watermark embedding step of selectively altering the original picture~~  $LL_n$  coefficient value, ~~if in case the watermark value~~  $-1$  is ~~to be embedded in a corresponding pixel embedded position~~  $i$ , the original picture coefficient value  $LL_n(i)$  is compared with ~~[[a]] an added~~ value  $LL'_n(i) + \lambda(i)$  obtained by adding the embedment strength to the mirror picture coefficient value ~~and such that~~

if the original picture coefficient value is greater ~~[[more]]~~ than the added value, the original picture coefficient value is maintained as ~~[[it]]~~ is, and

if the original picture coefficient value is less than the added value, the original picture coefficient value of the pixel position is ~~substituted for~~ assigned the added value.

5. **(currently amended)** The method of claim 1, wherein, in the ~~watermark embedding step of selectively altering the original picture~~  $LL_n$  coefficient value, ~~if in case the watermark value~~  $-1$  is ~~to be embedded in a corresponding embedded pixel position~~  $i$ , the original picture coefficient value  $LL_n(i)$  is compared with ~~[[a]] a subtracted~~ value  $LL'_n(i) - \lambda(i)$  obtained by subtracting the embedment strength from the mirror picture coefficient value ~~and such that~~

if the original picture coefficient value is less than the subtracted value, the original picture coefficient value is maintained as ~~[[it]]~~ is, and

if the original picture coefficient value is greater ~~[[more]]~~ than the subtracted value, the original picture coefficient value is ~~substituted for~~ assigned the subtracted value ~~for alteration~~.

6. **(currently amended)** The method of claim 1, wherein the initial original picture efficient value is maintained to skip ~~[[in]]~~ the watermark embedment at each pixel position where the original picture  $LL_n$  coefficient value before and after said altering differs by ~~embedding skipping step, in case the original picture coefficient value altered by the watermark embedment is differentiated from an initial original picture coefficient value before the watermark embedment at more than three times the embedment strength, the initial original picture efficient value is maintained to skip the watermark embedment.~~

7. **(currently amended)** The method of claim 1, wherein ~~in the watermark embedding step,~~ the watermark ~~sequence~~ is repetitively embedded in each pixel ~~embedded~~ position a ~~at~~ a predetermined number of times ~~being set~~ depending on robustness and screen degradation degree.

8-9. (canceled)

10. **(new)** A watermark extracting method of extracting a watermark embedded by the method of claim 1 from a watermark embedded image, the watermark extracting method comprising the steps of:

wavelet transforming the watermark embedded image into the same n levels;

defining a wavelet lowest subband of the wavelet-transformed watermark embedded image as a watermark extracted region;

high-frequency filtering an original picture  $LL_{nE}$  of the watermark extracted region to generate a mirror picture  $LL_{nE}'$  from which a high frequency component of the original picture  $LL_{nE}$  has been eliminated;

receiving index information designating a plurality of pixel positions within the watermark extracted region where the watermark has been embedded;

comparing an original picture  $LL_{nE}$  coefficient value with a mirror picture  $LL_{nE}'$  coefficient value at each said pixel position to extract a sequence  $W_E(i)$  of watermark values;

receiving a key value to regenerate an original sequence  $W(i)$  of watermark values used at the time of watermark embedment; and

determining a similarity between the extracted watermark sequence and the original watermark sequence, and judging whether or not the watermark exists depending on whether or not the similarity is greater than a predetermined critical value.

11. **(new)** The method of claim 10, wherein, in the watermark extracting step,

Serial No. 10/734,142

if the original picture  $LL_{nE}$  coefficient value is less than the mirror picture  $LL_{nE}'$  coefficient value, a watermark value  $-1$  is extracted from the respective pixel position;  
otherwise, a watermark value  $+1$  is extracted.